








STAINLESS STEEL DUPLEX PRESSURE GAUGE, TYPE PBB

TYPE PBB, with double bourdon-tube and two pointers

STANDARD MODEL

CASE	: bayonet lock, AISI304/1.4301, IP-65 standard with blow-out	RANGES	: -1/0 and 0-0,6 - 60 bar, acc. to EN 837-1 (see page 55) for higher ranges (max. 1600 bar), see page 55
WETTED PARTS	: double bourdon tube AISI316Ti/1.4571	MOVEMENT	: brass
WINDOW	: mineral 4 mm	ACCURACY	: Ø 100 and Ø 160 mm± 1.0% F.S./class 1.0
DIAL	: aluminium, black figures on white	APPLICATIONS	: general industry
POINTERS	: two pointers, 1x black and 1x red, aluminium	OPTIONS	: see page 57-58, electrical contact or transmitters
CONNECTION	: Ø100 and Ø160 mm : 2x ½"BSP or ½"NPT		4-20mA, 0-20mA, 0-10Vdc see page 59-65

TYPE	MODEL	CASE DIAMETER xxx (Ø in mm)	
		100	160
K		PBB100XK	PBB160XK
L		PBB100XL	PBB160XL
M		PBB100XM	PBB160XM
N		PBB100XN	PBB160XN
O		PBB100XO	PBB160XO
H		PBB100XH	PBB160XH
OPTION		EXTRA COSTS	
Lx	LIQUID FILLED CASE: GLYCERINE (in combination with electrical device: Ondina oil see page 64)	PBB100Lx	PBB160Lx
DIFFERENTIAL SCALE	 SMALL SCALE IN CENTER TO READ DIFFERENTIAL PRESSURE		
"Hz" CONTACT DEVICE	EXCLUDING "Hz" CONTACT: ONLY POSSIBLE ON ONE POINTER (see page 59-63)		