

"CLASS 0,25 TEST PRESSURE GAUGES, TYPE PBX-TG

TYPE PBX-TG, with bourdon tube of copper-beryllium

STANDARD MODEL

CASE	: bayonet lock, AISI304/1.4301, IP-65, blow-out
BOURDON TUBE	: Copper/Beryllium
WINDOW	: mineral glass 4 mm
DIAL	: Mirrorscale aluminium, black figures on white
POINTER	: knife edge aluminium, black
CONNECTION	: ½"BSP or ½"NPT, AISI316Ti/1.4571
RANGE	: from 0 - 1 upto 0-60 bar, acc. to EN 837-1 or from 0-15 psi upto 1.000 psi
ACCURACY	: 0,25% F.S. / class 0,25
MOVEMENT	: stainless steel AISI304/1.4301
CALIBRATION REPORT	: included, minimal 10 points
OPTIONS / GRADUATIONS	: see page 55-58



TYPE	MODEL	CASE DIAMETER (Ø in mm)		
		160	200	250
A		PBX-TG-160XA	PBX-TG-200XA	PBX-TG-250XA
B		PBX-TG-160XB	PBX-TG-200XB	PBX-TG-250XB
C		PBX-TG-160XC	PBX-TG-200XC	PBX-TG-250XC
D		PBX-TG-160XD	PBX-TG-200XD	PBX-TG-250XD
F		PBX-TG-160XF	PBX-TG-200XF	PBX-TG-250XF
H		PBX-TG-160XH	PBX-TG-200XH	PBX-TG-250XH
J		PBX-TG-160XJ	PBX-TG-200XJ	PBX-TG-250XJ
OPTIONS		EXTRA COSTS		
HIGHER RANGES	0-100 bar / 0-1.500 psi			
	0-160 bar / 0-2.000 psi			
	0-250 bar / 0-3.000 psi			
	0-400 bar / 0-6.000 psi			
	0-600 bar / 0-10.000 psi			
	0-1000 bar / 0-15.000 psi			
DOUBLE SCALE	bar / psi bar / kPa ect.			